TOTAL NETWORK SOLUTIONS

ORDERING INFORMATION

Model	Description
CLD-221P	Power NAS (Network Attached Storage) with Print Server/LCD Display

DESCRIPTION

CLD-221P is a NAS/USB Dual Function Storage with luminous blue color LCD screen. Adopting embedded Linux operating system architecture, It is a low power consumption, low cost, high performance digital gadget perfectly for home users. **CLD-221P** is an elegant information gadget with digital stylish design. The LCD screen can indicate some system information, such as current IP address used by **CLD-221P**, NAS/USB mode indicator, HDD capacity usage status, system temperature, system fan speed, and operating time after starting the device. Build-in Print Server provides maximum usability with minimum cost for the customers.

KEY FEATURES

- A Luxury USB2.0 HDD External Enclosure with NAS Function
- Equipped with LCD System Status Screen
- Sharing the video, audio, and other data formats on the LAN
- Simple configuration to setup FTP and Samba Servers
- Acting either as a external USB drive or a network storage
- ATA interface and supports up to 480GB hard disk
- Build-in FTP Server for cross border file sharing
- With SMB mechanism to easy maintain the device
- Build-in Print Server for easy print job
- Speed up to 6 MB

Specifications are subject to change without notice Trademarks & Trade Names belong to their owners

PRODUCT SPECIFICATIONS

Model Number	CLD-221P
CPU	ARM 9 200MHz RISC Processor
Flash	8MB Flash ROM
RAM	64MB DDR SDRAM
Hard Disk Support	One 3.5” IDE HDD (FAT32/EXT3)*
Hard Disk Interface	Ultra DMA/133, Conforms to ATA-6 Spec.
LAN Interface	10/100Mbps auto-sensing RJ-45 connector
USB Interface	USB2.0 Client
Print Server Interface	USB1.1 Host
LCD Dimension	73mm*29mm
Operating System	Microsoft Windows: 98SE, ME, 2000, XP Mac OS9 / Mac OSX Linux
Network Protocol	TCP/IP, Samba Server, NFS Server, Window Network, DHCP Server/Client (Auto detection), Macintosh Bonjour, Apple Talk, SNTP Client, FTP server
DHCP (client) Support	Yes
Management	Web interface
Firmware Upgradeable	Yes, via Web interface
Operating Temperature	0~60°C
Operating Humidity	0~70% Non Condensing
Dimension	195(L) x 174(W) x 52.5(H) mm
Weight	0.60kg
Power Supply	DC 12V/5V, 2A
* Hard Drive sold separately	

Specifications are subject to change without notice Trademarks & Trade Names belong to their owners